

NL2 Millennium Series

- Fully automatic FMVSS 403 compliant lift, operated by an attendant
- Loading position either direction
- Interfaces with OEM interlocks
- Long lasting LED lift mounted lights that are active when vehicle interlocks are engaged and lift power switch is on
- Hand-held control box with illuminated functions
- Locking mechanical Inboard Barrier (IB), powder coated yellow for safety and high visibility, prevents operation if occupied
- Pump design prevents platform folding when occupied, quiet operation & low current draw
- Durable redesigned baseplate reduces lift weight and allows for quicker and easier service of hose/wiring
- Easily installed, step-by-step installation instructions, no peripheral hardware required
- Platform movement prevented during unsafe operation
- Hydraulic outer barrier that will be in the fully up position before the platform leaves the ground, complete with durable rubber nose guard
- Transition areas marked with durable high-gloss yellow powder coating for safety & visibility
- Side or rear door application
- Several platform widths and lengths
- Dual handrails for security and convenience
- Bridging feature permits the wheelchair user to board the lift from sidewalks or inclines
- Floor to ground travel is 42" or 48"
- Lifting capacity is 800 lbs
- Integrated back-up pump
- Equipped with an adjustable anti-rattle feature to avoid unpleasant noise in the vehicle during transit
- Durable high-gloss powder coated finish
- Lift-Tite system stows the lift platform securely while the vehicle is in transit
- Pump module with removable cover offers easy access to all components
- Optional handrail belt





Integrated dual handrails provide added security for wheelchair users and standees





Visual and audible warnings alert both passengers and attendants to unsafe conditions

Hydraulic roll stop engages and locks before the platform leaves the ground





631 West 11th Street • Winamac, IN 46996 (574) 946-6153 • 1-800-THE-LIFT www.braunability.com/commercial